

SR-54M-HLPROD MONO

Sunrise Energy Co., a Leading PV Company in Solar Panel Manufacturing ,Solar Project Investment and Solar System Integration.

Excellent technical advantages and system design scheme to achieve high reliability, power generation effective gain and EPC cost reduction. Products can match different installation conditions, taking into account high

adaptability and high compatibility.

With mature support and inverter scheme, customized design for industrial and commercial and centralized ground power stations.

Product advantage of Sunrise Energy SR-M672HLPro solar modules:

- 0 +5 W positive tolerance guarantee
- The use of high light transmission and reflection reduction 3.2mm glass, low light environment electric performance is stronger
- PID attenuation can be minimized under conventional conditions
- Salt mist / Ammonia / Dust and Hail resistance
- IEC61215 / IEC61730 / ISO9001 / ISO14001 / ISO45001 Certifications
- The Half cut cell size M10 using Multiple Bus Bar, which can eliminate the chamfering loss of single crystal
- Reduce BOS cost increase ROI



High Power Output.



Better Low-Light performance..



MBB Half Cut Cell Technology



Less Shading Effect



0 + 5 W Positive Tolerance



PID Resistance

SPECIFICATIONS

SR-54M435NHLProD 435 W SR-54M440NHLProD 440 W SR-54M445NHLProD 445 W SR-54M450NHLProD 450 W									
Number of cells		108 (6 x 18)							
Cell type		M10 Monocrystalline - 182 x 91 mm (Multiple Bus Bar)							
Maximum system voltage		1500 Vdc							

Electrical Specifications *									
		STC *	NOCT **	STC *	NOCT **	STC *	NOCT **	STC *	NOCT **
Maximum power	Pmax	435 Wp	328,16 Wp	440 Wp	331,93 Wp	445 Wp	335,70 Wp	450 Wp	339,48 Wp
Tolerance		0 / +5 W		0 / +5 W		0 / +5 W		0 / +5 W	
Maximum power voltage	Vmpp	32,05 V	30,07 V	32,24 V	30,25 V	32,43 V	30,43 V	32,62 V	29,31 V
Open circuit voltage	Voc	38,79 V	37,05 V	39,02 V	37,27 V	39,25 V	37,49 V	39,48 V	37,71 V
Maximum power current	Ipp	13,58 A	10,95 A	13,65 A	11,01 A	13,73 A	11,07 A	13,80 A	11,13 A
Short circuit current	Isc	14,34 A	11,58 A	14,42 A	11,64 A	14,50 A	11,71 A	14,48 A	11,77 A
Module efficiency		21,79 %		22,05 %		22,30 %		22,55 %	

Temperature Ratings									
Open circuit voltage coefficient	Tk Voc	-0,29 % / °C							
Short circuit current coefficient	Tk Isc	0,045 % / °C							
Power coefficient	Tk W	-0,25 % / °C							
Operating Temperature	NOCT	45 °C ±2 °C							

Other specifications									
Dimmensions		1762 x 1133 x 30 mm							
Weight		21 Kgr.							
Connection box		IP67 - 3 diodes Junction box							
Cable		Cable 4 mm2 - 1000 mm							
Connector		MC4 or MC4 compatible							

* STC (Standard Test Conditions: 1000 W/m2, 25° C, AM 1,5)
** NOTC (Normal Operating Test Conditions: 800 W/m2, 20° C, Windspeed 1 m/s)

DOWNLOADS

SR-54M-NHLPROD ESP

 N-type M10 108 cells 430~450w doble
ital Monofacial Bornay ESP.pdf

Size: 1.53 MiB

SR-54M-NHLPROD ENG

 N-type M10 108 cells 430~450w double
ss Monofacial Bornay ENG.pdf

Size: 1.54 MiB